




ISO & PG step drill bit Ø 10 mm 12 steps
Ideal for electricians!



Characteristics

Drilling Ø (mm): 6.5-32.5
Shank Ø (mm): 10
Hardness (HRC): 65-66
Numbers of floors : 12

Materials

- ☑ Metal
- ☑ Stainless steel

Benefits

- Fast chip evacuation by helix flute increases cutting capacity.
- 5 % cobalt steel for constant drilling temperature and for long life.
- Drilling accuracy with offset point.

GENERAL INFORMATION

Description

Compatible with PG and ISO.
12 laser marked steps.
Three flats milled on Ø 10 mm shank to prevent slipping in the chuck.

Technical details

Hexagonal shank 10 mm Ø.
5 % cobalt HSS steel.
Helix flutes.
Cross shaped sharpening.

Advices

Use cutting oil to extend the tool's lifetime.

Application(s)

Drills through metal sheet up to 4 mm thick.
For drilling non-ferrous metals, stainless steel and synthetic materials up to 4 mm thickness.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm) : 5
Length (cm) : 11,5
Depth (cm) : 5
Net weight (kg) : 0,197
Gross weight (kg) : 0,25



Outer package 1



Carton box

Height (cm) : 38,8
Length (cm) : 28,8
Depth (cm) : 19
Net weight (kg) : 10
Gross weight (kg) : 10,4



x 50.00