ISO & PG step drill bit Ø 10 mm 12 steps

Ideal for electricians!







Caracteristics

Drilling Ø (mm): **6.5-32.5 Shank** Ø (mm): **10 Hardness** (HRC): **65-66** Numbers of floors: 12

- Fast chip evacuation by helix flute increases cutting capacity.
- 5 % cobalt steel for constant drilling temperature and for long life.

Materials

Benefits

- Drilling accuracy with offset point.

GENERAL INFORMATION

Description

Compatible with PG and ISO. 12 laser marked steps. Three flats milled on Ø 10 mm shank to prevent slipping in the chuck.

Technical details

Hexagonal shank 10 mm Ø. 5% cobalt HSS steel. Helix flutes. Cross shaped sharpening.

Advices

Use cutting oil to extend the tool's lifetime.

Application(s)

Drills through metal sheet up to 4 mm thick. For drilling non-ferrous metals, stainless steel and synthetic materials up to 4 mm thickness.

LOGISTIC INFORMATION

Packaging



Plastic box

Height (cm): 5 Length (cm): 11,5 Depth (cm): 5 **♣ Net weight (kg):** 0,197

♣ Gross weight (kg): 0,25



Outer package 1



Carton box

Height (cm): 38,8 Length (cm): 28,8 **Depth (cm):** 19 Net weight (kg): 10





