

Wires pulling lubricating gel BIZ'RED 1L



Benefits

- Non-flammable, non-corrosive, non-toxic.
- No stickiness.

GENERAL INFORMATION

Technical details

Neutral pH 7.0 +/- 0.5.
 Usage temperature (°C) : -10 to +80.
 Storage temperature (°C) : -5 to +40 (freezes at -10 °C).
 Density (g/ml) : 1.04 +/- 0.05.
 Viscosity: 4500 +/- 500 cps.
 Dry residue (%) : 18.
 Volume (l) : 1.

Application(s)

To ease passage of cables and wires through electrical conduits, ducts and pipes.

Instructions

1. Plug gel at the entry to the duct and then feed in the cable, which will be lubricated 360°.

LOGISTIC INFORMATION

Packaging



Plastic bottle

Height (cm) : 29
 Length (cm) : 8
 Depth (cm) : 8
 Net weight (kg) : 1
 Gross weight (kg) : 1,05



Outer package 1



Carton box

Height (cm) : 31
 Length (cm) : 34,5
 Depth (cm) : 25,5
 Net weight (kg) : 12
 Gross weight (kg) : 13,05



Outer package 2



Pallet

Height (cm) : 110
 Length (cm) : 120
 Depth (cm) : 80
 Net weight (kg) : 324
 Gross weight (kg) : 367,35

